

Hush Silk Technical Sheet



Hush Silk Cobalt Wallpaper

Composition	100% Natural Silk on Non-woven Wallpaper
Width	34.2" / 87CM
Pattern Repeat	Vertical Repeat 36.2" / 92CM (Straight Match)
Roll Length	Max size 30 metre / 32 yard rolls (sold by linear metre / yard)
Weight	230 g/m ²
Minimum order	1M / 3 Yards
Fire Rating	EU Class B-S2-D0 - US Class A for ASTM-84
Lightfastness	Good
Maintenance	We do not recommend cleaning silk wallcoverings with water or other liquids because cleaning may damage or stain the face of the wallpaper. Try to remove any stains immediately, before the stain can dry out, by dabbing off the surface with a lint-free, clean white cloth. Avoid excessive rubbing or soaking of the surface. Lightly vacuum with a soft bristle to remove surface dirt and dust.
Commodity Code	48149070
Country of Origin	Italy

Inquire for custom projects No minimum order on standard wallpaper, vinyl, linen, cotton or Trevira.

Custom lead time 2-3 weeks sampling, 4-8 weeks production from receipt of 50% deposit.

Inquire for contract projects 40 Metre minimums for Performance Polyester FR, 100 Metre minimums for ASTM Vinyl.

Contract lead time 6-8 weeks sampling, 8-10 weeks production from receipt of 50% deposit and confirmed order.

IMPORTANT HANGING INFORMATION


Before you start please ensure the following:

- The wallcoverings are as ordered - as specified, as labelled (identification samples available immediately)
- You have sufficient material to complete the job in the same batch
- Batch numbers are identical - never mix batches on the wall, never in fill with off-cuts
- The correct adhesive for your individual site circumstances
- Adequate site conditions – good lighting for correct inspection, minimum ambient temperature of 10°C. Good ventilation & clean working conditions.
- Avoid excessive ambient temperatures – radiators should ideally be removed before and for the 24 hours after hanging. If this is not possible they must be turned off and kept off until the wallcovering has fully dried.

SURFACE PREPARATION

Correct identification of surfaces, and the appropriate preparation is critical to successful hanging. All surfaces should be:

- **Clean** – Remove all surface contamination, e.g dirt, grease and pigmented marks, eg felt pen etc. Wash off using a detergent solution, rinse and allow to dry thoroughly.
- **Sound & Even** – Free of flaking paint, old wallpaper/backing. Evidence of previous adhesive should be removed with hot water. Weak skims/ surfaces and uneven surfaces will require remedial action.
- **Uniform in Colour** – To prevent show through equalise colour.
- **Dry in Depth** – Tested with good moisture meter.
- **Keyed** – With coarse, dry sandpaper.
- **We recommend the use of a lining paper.**
- **After hanging 3 drops, check the result after 24 hours.**

RECOMMENDED ADHESIVE	APPLY TO	METHOD OF JOINT	PRODUCT INFORMATION	WHERE TO BUY
Ready Mixed Metylan Ovalit (Use a vinyl ready to use paste for non-woven based wallpapers)	Apply to the wall	Paste the wall + Butt Join	This product is hung by applying an even coating of paste on the wall. Avoid squeezing the paste between the edges of the paper. The paste must not come into contact with the surface of the paper at any time. All traces of paste must be removed before drying by dabbing lightly the surface with a moist, clean sponge. If paste dries on the surface of the wallpaper it will cause discoloration.	Click here 

This information is supplied in good faith, but without guarantee and on the understanding that the installer will have decorating knowledge to work with differing site or atmospheric conditions.